

SECTION 1: IDENTIFICATION

Product Name SMRT ATEX

Address Marshall House, Zarya Court, Grovehill Road, Beverley, HU17 0JG, United Kingdom.

 Telephone Number
 +44 (0)1482 679 300

 Fax Number
 +44 (0)1482 679 145

 Email Adddress
 sales@mrtsos.com

Date of Issue July 2023

Issue Number 2

Description The sMRT ATEX life jacket and PLB solution is easy to use, auto activates and monitors the

safety of your crew 24/7. The SOLAS approved life jacket inflates and activates the sMRT

ATEX approved PLB as it hits the water.

BATTERY SHIPPING INFORMATION: UN3091 LITHIUM METAL BATTERIES CONTAINED IN EQUIPMENT IN COMPLIANCE WITH IATA PI: 970 SECTION II.





SECTION 2: SPECIFICATION

KEY FEATURES

- Durable waterproof fabric
- Durable wipe clean PVC reinforcement
- Double shoulder straps for comfort and reduction of weight to the back neck.
- Zip fastening cover with snag proof press-stud security system for zip closures
- · Stainless steel interlocking belt buckles
- · Adjustable waist belt
- · Detachable crutch strap
- 2 Inflation systems operational readiness indicator windows on the back
- · Beacon access zip on front
- · Service date information window on the back
- Black/silver chequered retro-reflective tap on the upper chest
- · Additional foam and double fabric padding layer to protect the beacon inside the cover

INFLATABLE BLADDER

- · Double chamber
- Oral inflation tube on back chamber and Over pressure tube + relief valve on front chamber for manual inflation and deflation and also to relieve any excess pressure if both chambers are fired simultaneously
- · SOLAS approved retro-reflective tape on bladder
- Red recovery grab strap on bladder marked "LIFT"
- 2 x 60g CO2 gas cylinders
- · Automatic water-activated SOLAS S.O.S. light
- 2 x Safety indicator Inflation systems
- · Marine grade whistle
- Buddy line

ACTUAL BUOYANCY

• 320N

AVAILABLE SIZES

Universal

CERTIFIED

- SOLAS
- EN ISO 12402-2 : 2006 +A1 : 2010 EN ISO 12402-6: 2006 + A1:2010 for inflatable lifejackets performance level 275

COLOUR

· RS0 Red

PERSONAL LOCATOR BEACON

• The sMRT AU10 beacon will send a distress signal to a local receiver (vessel). The beacon will activate by means of full water immersion. Frequencies 121,5MHz and AIS

AVAILABLE INFLATION SYSTEMS

2MTKF3NM1: United Moulders Pro Sensor Elite auto inflator

ATEX APPROVAL

· Fitted with ATEX approved light



